



	TG 16 PRO S	TG 22 PRO S	TG 25 PRO S	TG 28 S	TG 35 S	TG 42 S	TG 42 SM	TG 55 S	TG 55 SM	TG 80 SM
A	36,6	47,2	52,8	58,7	74	72,1	72,1	96	96,3	122,6
B	20,3	24,5	28,5	30,9	31,8	38,7	38,7	40,4	40,4	44,3
C	14	17,6	19,6	22,4	23,4	26,6	26,6	31,6	31,6	61,9
D	1,9	2,6	2,8	3,9	2,6	3,9	3,9	5,9	5,9	7,1
E	13,5	17	19	20	20,6	21	21	24,9	24,9	39,8
F	140x140-17	173/6-17 & 140x140-17	173/6-17 & 140x140-17	173/6	173/6	173/6	270/8	270/8	270/8	270/8

MODEL SPECIFICATIONS



Model	Weight (lb)	Capacity (sq ft)	Pressure (psi)	Flow Rate (gpm)	Force (lbf)	Capacity (lb)	Capacity (lb)	Capacity (lb)
TG 16 PRO S	168	1,72	2900	13,3	1570	2205-8820	2205-13230	2205
TG 22 PRO S	317	2,15	3625	13,3	3260	8820-17640	8820-26460	6615
TG 25 PRO S	459	2,42	3625	13,3	3260	13270-22050	13230-33075	8820
TG 28 S	606	3,23	4350	16	3730	17640-26460	17640-39690	11025
TG 35 S	750	4,09	4350	16	3930	22050-35280	22050-48510	15435
TG 42 S	899	5,38	4350	18,7	4900	26460-39690	26460-55125	17640
TG 42 SM	1102	7	4350	18,7	4900	33075-55125	33075-66150	22050
TG 55 S	1675	7	4350	24	5620	35280-44100	35280-66150	22050
TG 55 SM	2083	7	4350	24	5620	44100-66150	44100-77175	22050
TG 80 SM	2222	8,61	4350	24	8990	33075-55125	33075-77175	22050